

BG Coatings PTY Ltd



SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BG Pool Paint – Top Coat Part A

Synonyms

BG Pool Epoxy Pool paint - Light Jade 2.625L
BG Pool Epoxy Pool paint - Crisp White 2.625L
BG Pool Epoxy Pool paint - Aqua Fresh 2.625L
BG Pool Epoxy Pool paint - Sea Green 2.625L
BG Pool Epoxy Pool paint - Coral Sea 2.625L
BG Pool Epoxy Pool paint - Marine 2.625L
BG Pool Epoxy Pool paint - Ice Blue 2.625L
BG Pool Epoxy Pool paint - Tropical Blue 2.625L
BG Pool Epoxy Pool paint - Cyan Blue 2.625L
BG Pool Epoxy Pool paint - Ocean Blue 2.625L
BG Pool Epoxy Pool paint - Charcoal 2.625L
BG Pool Epoxy Pool paint - Maritime Blue 2.625L
BG Pool Epoxy Pool paint - Sandy Bay 2.625L
BG Pool Epoxy Pool paint - Sandstone 2.625L
BG Pool Epoxy Pool paint - Moss Green 2.625L
BG Pool Epoxy Pool paint - Olive Green 2.625L
BG Pool Epoxy Pool paint - Tropical Green 2.625L
BG Pool Epoxy Pool paint - Poseidon 2.625L
BG Pool Epoxy Pool paint - Gulf Blue 2.625L
BG Pool Epoxy Pool paint - Watermark 2.625L
BG Pool Epoxy Pool paint - Grey Aqua 2.625L
BG Pool Epoxy Pool paint - Raven Black 2.625L
BG Pool Epoxy Pool paint - Willow 2.625L

Product Code

E-P-LigJ-2.625L
E-P-CriW-2.625L
E-P-AquF-2.625L
E-P-SeeG-2.625L
E-P-CorS-2.625L
E-P-Mari-2.625L
E-P-IceB-2.625L
E-P-TroB-2.625L
E-P-CyaB-2.625L
E-P-OceB-2.625L
E-P-Char-2.625L
E-P-MarB-2.625L
E-P-SanB-2.625L
E-P-SanS-2.625L
E-P-MosG-2.625L
E-P-OliG-2.625L
E-P-TroG-2.625L
E-P-Pose-2.625L
E-P-GulB-2.625L
E-P-Wate-2.625L
E-P-GreA-2.625L
E-P-RavB-2.625L
E-P-Will-2.625L

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Epoxy Top Coat - Base Component for swimming pools, ponds and fountains.

Supplier detail

Company Name BG Coatings)Pty) Ltd.
Address U4/34 Truganina Road.
Malaga, Perth.
Western Australia.
6090
Emergency Telephone 1300-894-994
Facsimile
National Contact Mr A Schule

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



SECTION 2. HAZARD IDENTIFICATION

Hazardous according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS)

Classification of the substance or mixture

Flammable liquids – Category 3

Acute toxicity, oral – Category 4

Acute toxicity, dermal – Category 4

Skin corrosion/irritation – Category 2

Serious eye damage/eye irritation – Category 2

Acute toxicity, inhalation – Category 4

Specific target organ toxicity, single exposure; Respiratory tract irritation – Category 3

Specific target organ toxicity, single exposure; Narcotic effects – Category 3

Pictograms



Signal word

Warning

Hazard Statements

- AUH066 Repeated exposure may cause skin dryness or cracking.
- H226 - Flammable liquid and vapour.
- H302 - Harmful if swallowed.
- H312 - Harmful in contact with skin.
- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H332 - Harmful if inhaled.
- H335 - May cause respiratory irritation.
- H336 - May cause drowsiness or dizziness.

Precautionary Statements

- Prevention
- P101 - If medical advice is needed, have product container or label at hand.
 - P102 - Keep out of reach of children.
 - P103 - Read label before use.
 - P210 - Keep away from heat/sparks/open flames/hot surfaces
- No smoking.
 - P233 - Keep container tightly closed.
 - P241 - Use explosion-proof electrical/ventilating/lighting/.../equipment,
 - P242 - Use only non-sparking tools.
 - P243 - Take precautionary measures against static discharge.
 - P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P264 - Wash hands thoroughly after handling.
 - P270 - Do not eat, drink or smoke when using this product.
 - P271 - Use only outdoors or in a well-ventilated area.
 - P280 - Wear protective gloves/protective clothing/eye protection/
face protection.
 - P281 - Use personal protective equipment as required.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



Response	P301 + IF SWALLOWED: Immediately call a POISON CENTER or doctor/ P310 - physician. P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302 + P352 - IF ON SKIN: wash with plenty of soap and water. P303 + P361 + IF ON SKIN (or hair): Remove/Take off Immediately all P353 - contaminated clothing. Rinse SKIN with water/shower. P304 + IF INHALED: Remove victim to fresh air and Keep at rest in P340 - a position comfortable for breathing. P305 + IF IN EYES: Rinse cautiously with water for several minutes. P351 + Remove contact lenses, if present and easy to do, continue P338 - rinsing. P309 + IF exposed or if you feel unwell: call a POISON CENTER or P331 - doctor/physician. P332 + P313 - IF SKIN irritation occurs: Get medical advice/attention. P337 + P313 - IF eye irritation persists: Get medical advice/attention. P370 + In case of fire: Use carbon dioxide (CO ₂), dry chemical, regular P378 - foam extinguishing agent or water spray for extinction. P391 - Collect spillage. Hazardous to the aquatic environment.
Storage	P403 + P235 - Store in a well-ventilated place. Keep cool.
Disposal	P501 - Dispose of contents/containers in accordance with local regulation.

Other hazards which do not Result in classification: None identified.

SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

CAS number/other identifiers

Chemical entity	CAS number	% (weight)
Dimethylbenzene	1330-20-7	10-15
Ethylbenzene	100-41-4	1-5
1-Methoxy-2-propanol	108-65-6	1-5
Acetic acid, butyl ester	123-86-4	1-5
2-Butonone	78-93-3	<1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in section 8.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



SECTION 4. FIRST AID MEASURES

Description of necessary measures according to routes of exposure.

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persists.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	Remove contaminated clothing and shoes. Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Continue to rinse for at least 10 minutes. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/ effects, acute and delayed

Potential acute health effects

Eye contact	Causes serious eye irritation.
Inhalation	Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Ingestion	Harmful if swallowed. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include pain or irritation, watering or redness.
Inhalation	Adverse symptoms may include nausea or vomiting, headache, respiratory irritation, drowsiness/fatigue or dizziness/vertigo.
Skin contact	Adverse symptoms may include irritation or redness.
Ingestion	May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
--------------------	---

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



<p>Specific treatments Protection of first-aiders</p>	<p>No specific treatment. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.</p>
---	---

See toxicological information (Section 11)

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing media

<p>Suitable extinguishing media</p>	<p>Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO₂, water spray (fog) or foam. Use fog to cool and control.</p>
<p>Unsuitable extinguishing media</p>	<p>Do not use water jet.</p>

Specific hazards arising from the chemical

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
Carbon dioxide
Carbon monoxide
Metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

<p>For non-emergency personnel</p>	<p>No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material.</p>
------------------------------------	--

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



Conditions for safe storage, Including any Incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits.

Ingredient	Material name	TWA	STEL
Dimethylbenzene	Xylene	80 ppm (350 mg/m ³)	150 ppm (655 mg/m ³)
Ethylbenzene	Ethyl Benzene	100 ppm (434 mg/m ³)	125 ppm (543 mg/m ³)
1-Methoxy-2-propanol	Methoxy Propyl Acetate	50 ppm (274 mg/m ³)	100 ppm (548 mg/m ³)
Acetic acid, butyl ester	n-Butyl Acetate	150 ppm (713 mg/m ³)	200 ppm (950 mg/m ³)
2-Butonone	Methyl ethyl ketone	150 ppm (713 mg/m ³)	300 ppm (890 mg/m ³)

Recommended monitoring Procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



Hand protection:

Avoid direct contact. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Avoid direct contact. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous liquid.
Colour:	Coloured liquid.
Odour:	Characteristic odour.
Solubility in water:	Immiscible.
Specific Gravity:	1.450 – 1.540
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	Not available.
Flash Point	27°C
Lower and upper explosive (flammable) limits:	Not available.
Auto ignition Temperature (°C):	Not available.
Volatile component (% vol)	40
Solubility in water (g/L):	Immiscible.
Melting Point/Freezing point (°C):	Not available.
Boiling Point/Range (°C):	Not available.
Decomposition Point (°C):	Not available.
PH:	Not available.
Viscosity (cSt):	Not available.
Evaporation Rate:	Not available.
VOC g/L:	321

SECTION 10. STABILITY AND REACTIVITY

Chemical stability:	The product is stable under normal conditions of use. Inert - no reaction with fire-fighting water.
Conditions to avoid:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Containers, even those that have been emptied, may contain explosive vapours.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



- Incompatible materials:** Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.
- Hazardous decomposition products:** Combustion products include: carbon dioxide (CO₂) and other pyrolysis products typical of burning organic material.
- Hazardous reactions:** Avoid reaction with amines, mercaptans, strong acids and oxidising agents. Violent reactions which may lead to ignition and explosion may occur.
If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Substance	Result	Species	Dose	Exposure
Dimethylbenzene	LD50 Oral	Rat	4300 mg/kg	-
	LC50 Inhalation Gas	Rat	5000 ppm	4 hours
Ethylbenzene	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
1-Methoxy-2-propanol	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Acetic acid, butyl ester	LD50 Oral	Rat	10760 mg/kg	-
	LD50 Dermal	Rabbit	14112 mg/kg	-
	LC50 Inhalation	Rat	> 21,0 mg/l	4 hours
2-Butonone	LD50 Oral	Rat	2600 mg/kg	-
	LC50 Inhalation	Rat	>5000 ppm	-
	LD50 Dermal	Rat	6400 mg/m ³	-

Information on the likely routes of exposure: Inhalation, ingestion, skin and eye contact

Potential acute health effects

- Eye contact : Causes serious eye irritation.
- Skin contact : Harmful in contact with skin. Causes skin irritation.
- Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.
- Ingestion : Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact : Adverse symptoms may include pain or irritation, watering or redness.
- Skin contact : Adverse symptoms may include irritation or redness. Blistering may also occur.
- Inhalation : Adverse symptoms may include nausea or vomiting, headache, respiratory irritation, drowsiness/fatigue or dizziness/vertigo.
- Ingestion : May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Substance	Result	Species	Dose
Dimethylbenzene	Acute: LC50 8.5 mg/L Marine water.	Crustaceans - <i>Alaemonetes pugio</i>	24 hours
	Acute: LC50 3.3 - 4.1 mg/L Fresh water.	Fish - <i>Oncorhynchus mykiss</i> - 0.6 g	96 hours
Ethylbenzene	Acute: EC50 4.6 mg/L	Algae - <i>Pseudokirchneriella</i> Subcapitata.	72 hours
	Acute EC50 3.6 mg/L	Algae - <i>Pseudokirchneriella</i> subcapitata.	96 hours
	Acute EC50 1.8 - 2.4 mg/L	Daphnia magna - <24 hours	48 hours
	Acute LC50 4.2 mg/L	Fish - <i>Oncorhynchus mykiss</i>	96 hours
1-Methoxy-2-propanol	Acute: LC50 161 mg/L	Pimephales promelas - Fathead minnow.	96 hours
	Chronic: LC50 63.5 mg/L	Oryzias latipes.	14 days
	Acute: LC50 408 mg/L	Daphnia manga.	48 hours
	Chronic: EC50 > 100 mg/L	Daphnia manga.	21 days
	Acute : EC50 > 1000 mg/L	Selenastrum capricornutum - Green algae.	96 hours
Acetic acid, butyl ester	Acute: LC50 18 mg/L	Fish - Fathead minnow	96 hours
	Acute: EC50 44 mg/L	Daphnia manga	48 hours
	Acute: EC50 674.7 mg/L	Algae - <i>Desmodesmus subspicatus</i>	72 hours
2-Butonone	Acute: LC50 3.130 – 3.320 mg/L	Fish - Fathead minnow	96 hours
	Acute: EC50 7.060 mg/L	Daphnia manga	24 hours

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Ecotoxicity: Do not allow the product to contaminate waterways.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

SECTION 13. DISPOSAL CONSIDERATIONS




Disposal methods : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1



SECTION 14. TRANSPORT INFORMATION

Designation	Land Transport (ADG)	Marine Transport (IMO/ IMDG)	Air Transport (IATA)
UN number	1263	1263	1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)		
Transport hazard class	3	3	3
Labels required			
Hazchem	•3Y	•3Y	•3Y
Packing group	III	III	III
Marine pollutant	No	No	No
Additional information	No data available.	Emergency schedules (EmS) F-E, S-E	No data available.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available.	No data available.	No data available.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product.

Information compiled with reference to raw material safety data sheets.

SECTION 16. OTHER INFORMATION

History

Date of printing : 11 Sept 2019

Date of previous issue : Not applicable.

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1

BG Coatings PTY Ltd



N.B. Technology may change with time necessitating changes to this Safety Data Sheet (SDS). It is the responsibility of the user to ensure that the latest SDS is being used.

MANUFACTURED BY BG COATINGS

U4/34 Truganina Rd
6090 Malaga
Australia

Should you have any queries or require any further information please contact the BG COATING advisory service:
Phone: 1300-894-994 **E-mail:** info@bgcoatings.com.au

Approval Date	03-Nov-2019
Effective Date	03-Nov-2019
Doc classification	Controlled Copy

Release Version	01
QMS Controlled by	Quality Manager
Document Ref	QMS-REC_1